

Mixed 2-Butenes



Mixed 2-Butenes is filled from bulk raw material sourced from a preferred partner and analysed to ensure compliance to our published specification.

Standard Specifications

| | |
|---------------------------|------------------|
| PURITY / ASSAY | 2.0 |
| IMPURITIES (MOL %) | >99.0% |
| Other Impurities | < 1 |

Standard Cylinder Sizes and Fill Volumes

CYLINDER INFORMATION

| CYLINDER SIZE | FILL VOLUME (KG) |
|---------------|------------------|
| L454 | 245.0 |
| L30 | 50.0 |
| L05 | 10.0 |
| L03 | 5.0 |
| L01 | 2.5 |
| LB | 0.25 |

* Dip tube available for liquid withdrawal

Technical Information

| TECHNICAL DATA | | SHIPPING INFORMATION | |
|---|----------------|----------------------|---------------|
| Molecular Weight (g/mol) | 56.107 | Shipping Name | Butylene |
| Liquid Density (kg/m³) | 641.2 | Hazard Class | 2.1 |
| Gas Density (kg/m³) | 2.442 | UN No. | UN 1012 |
| Boiling Point (0^c) | 3.7 | Hazard Label | Flammable Gas |
| Specific Volume (m³/kg) | 0.418 | CAS No. | 590-18-0 |
| Vapour Pressure (bar.a) | 0.89 | | |
| Valve Outlet | CGA 510 / BS 4 | | |

AGT INTERNATIONAL
AGT International provides businesses with Shorter lead times, Higher Inventory Levels, Guaranteed Quality and Lower Costs.

PRODUCTS

AGT International supplies a comprehensive range of hydrocarbon gases and liquids and associated special gases.

CYLINDERS

AGT International has a wide range of cylinders and bulk containers available for either purchase or rent as well as being able to fill customer owned cylinders.

CONTACT

Please contact us if the specification you require is not shown above. AGT International is able to custom manufacture different specifications according to your requirements.
<http://www.agti.biz/>